

NG2P

2-port terminal control valves PN16

Product features

DN15, DN20 and DN25 (straight)

Medium: water 2 – 95 °C (VDI 2035)

Kvs: adjustable ¹⁾

Brass

Threaded

Flat connections ISO 228-1

Types

Type	DN [inch]	Kvs [m ³ /h]	In	Out
NG2P15A	½"	1,6 ¹⁾	G½"	G½"
NG2P15B	½"	1,0 ¹⁾	G½"	G½"

BELPARTS Group NV

Wingepart 4
3110 Rotselaar
Belgium

T +32 (0)16 29 93 00
E info@dc.belparts.wphontwikkel.nl

belparts.com

1 / 3

All rights reserved © 2026 BELPARTS Group NV
Subject to modifications without prior notice.

Type	DN [inch]	Kvs [m³/h]	In	Out
NG2P15C	½"	0,63 ¹⁾	G½"	G½"
NG2P20A	¾"	3,5 ¹⁾	G¾"	G¾"
NG2P20B	¾"	2,5 ¹⁾	G¾"	G¾"
NG2P25A	1"	4,5 ¹⁾	G1"	G1"

¹⁾ Adjustable Kvs; see specifications

Specifications

Adjustable Kvs settings [m³/h]

NG2P15A: 0,2 - 0,63 - 1,0 - 1,3 - 1,5 - 1,6
NG2P15B: 0,2 - 0,3 - 0,4 - 0,63 - 0,85 - 1,0
NG2P15C: 0,2 - 0,4 - 0,5 - 0,55 - 0,6 - 0,63
NG2P20A: 1,0 - 1,9 - 2,5 - 2,9 - 3,1 - 3,5
NG2P20B: 0,3 - 1,1 - 1,9 - 2,2 - 2,4 - 2,5
NG2P25A: 1,0 - 1,9 - 3,0 - 3,9 - 4,2 - 4,5

Questions or request a quote for NG2P?

Our experts can help you with technical questions, product selection and provide a quotation for your project.

Ask a questionRequest a quote

BELPARTS Group NV

Wingepart 4
3110 Rotselaar
Belgium

T +32 (0)16 29 93 00
E info@dc.belparts.wphontwikkel.nl

belparts.com

2 / 3

All rights reserved © 2026 BELPARTS Group NV
Subject to modifications without prior notice.



+32 (0)16 29 93 00

BELPARTS Group NV

Wingepart 4
3110 Rotselaar
Belgium

T +32 (0)16 29 93 00
E info@dc.belparts.wphontwikk.nl

belparts.com

3 / 3

All rights reserved © 2026 BELPARTS Group NV
Subject to modifications without prior notice.